



MATERIAL SAFETY DATA SHEET

PRODUCT NUMBER: 11 20 31 / 11 20 32 / 11 20 33

SECTION 1 PRODUCT IDENTIFICATION AND MANUFACTURE

SUPPLIER: METPREP LTD.
CURRIERS CLOSE
CHARTER AVENUE
COVENTRY CV4 8AW

TELEPHONE: 024 7642 1222
FAX: 024 7642 1192

PRODUCT: EPO-MOUNT 2

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

Classification (GHS-US)

Carc. 2 H351
STOT RE 2 H373
Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms:

Signal word: Danger



GHS08

Hazard statements:

H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure
H232 - May form combustible dust concentrations in air

Precautionary statements:

P202 - Do not handle until all safety precautions have been read and understood
P264 - Wash hands, forearms and face thoroughly after handling
P273 - Avoid release to the environment
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P501 - Dispose of contents/container in accordance with all federal, state, and local health and environmental regulations.

2.3. Other hazards

Other hazards not contributing to the classification:

Phenol, formaldehyde, and ammonia vapors may be released during molding processes. Overexposure to these vapors may cause irritation to eyes, nose, throat, and skin. Sensitized individuals may experience allergic skin reactions. Exposure to dust from machining operations may cause nose and throat irritation. High concentration of airborne dust may form an explosive mixture with air. Ensure that good housekeeping practices are followed, as well as applicable guidelines such as National Fire Protection Association (NFPA) 654, "Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids.



SECTION 3 SUBSTANCE HAZARD IDENTIFICATION

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification
diatomaceous earth, uncalcined	(CAS No) 61790-53-2	10 - 20	STOT RE 2, H373
hexamethylenetetramine	(CAS No) 100-97-0	3 - 10	Flam. Sol. 2, H228 Skin Sens. 1, H317
carbon black	(CAS No) 1333-86-4	0.1 - 1	Carc. 2, H351

Full text of H-phrases: see section 16

4.1. Description of first aid measures

First-aid measures general:	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation:	Call a POISON CENTER or doctor/physician if you feel unwell. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact:	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact:	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion:	Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. Obtain emergency medical attention.

SECTION 4 FIRST AID MEASURES

4.1. Description of first aid measures

First-aid measures general:	Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation:	Call a POISON CENTER or doctor/physician if you feel unwell. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact:	Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact:	Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion:	Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries: Causes damage to organs.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available



SECTION 5 FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Foam. Dry powder. Carbon dioxide. Water spray.
Sand. Unsuitable extinguishing media: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Explosion hazard: high concentration of airborne dust may form an explosive mixture with air.

5.3. Advice for firefighters

Firefighting instructions: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

General measures: Remove ignition sources. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment: Equip cleanup crew with proper protection.
Emergency procedures: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: On land, sweep or shovel into suitable containers. Minimize generation of dust. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

Additional hazards when processed: Avoid breathing fumes from molding or other processes involving heat. Avoid breathing dusts from cutting, machining or de-flashing operations. Guard against dust accumulation of this material. High concentrations of airborne dust may form explosive mixture with air. As with all chemicals, good industrial hygiene practices should be followed when handling this material.



Precautions for safe handling:

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures:

Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures:

Proper grounding procedures to avoid static electricity should be followed.

Storage conditions:
cool.

Keep only in the original container. Keep container closed when not in use. Keep cool.

Incompatible products:
Incompatible materials:
sunlight. Storage area:

Keep only in the original container in a cool, well ventilated place away from Strong bases. Strong acids. Sources of ignition. Direct Store in cool, dry place.

7.3. Specific end use(s)

No additional information available

SECTION 8

EXPOSURE CONTROL/PERSONAL PROTECTION

8.1. Control parameters

BLACK EPOXY POWDER (COURSE/GLASS FILLED)		
ACGIH	Not applicable	
OSHA	Not applicable	
hexamethylenetetramine (100-97-0)		
ACGIH	Not applicable	
OSHA	Not applicable	
diatomaceous earth, uncalcined (61790-53-2)		
ACGIH	Not applicable	
OSHA	Remark (OSHA)	(3) See Table Z-3.
carbon black (1333-86-4)		
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³
ACGIH	Remark (ACGIH)	Bronchitis
OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³



8.2. Exposure controls

Personal protective equipment:	Avoid all unnecessary
exposure. Hand protection:	Wear protective gloves.
Eye protection:	Chemical goggles or safety glasses.
Respiratory protection:	Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear appropriate
mask. Other information:	Do not eat, drink or smoke during use.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state:	Solid
Appearance:	Black Colored Granules.
Color:	Black
Odor:	Characteristic
Odor threshold:	Characteristic odor Mild odor
pH:	No data available
Melting point:	No data
available Freezing point:	No data
available Boiling point:	No data
available Flash point:	No data
available Relative evaporation rate (butyl acetate=1):	No data
data available Flammability (solid, gas):	No data
available Explosion limits:	No data available
Explosive properties:	Mixtures of fine dust and air can create an explosion
hazard. Oxidizing properties:	No data available
Vapor pressure:	No data available
Relative density:	1.7 - 1.8
Relative vapor density at 20 °C:	No data available
Specific gravity / density:	1.7 - 1.8 g/cm ³
Solubility:	Water: Solubility in water of component(s) of the mixture : • hexamethylenetetramine: > 80 g/100ml • calcium hydroxide: 0.2 g/100ml • : insoluble • silicon dioxide, amorphous: 0.15 g/100ml • diatomaceous earth, uncalcined: insoluble • calcium stearate: 0.0040 g/100ml • stearic acid: 0.0003 g/100ml • : < 0.00001 g/100ml • : <0.01 g/100ml
Log Pow:	No data available
Log Kow:	No data
available Auto-ignition temperature:	No data
data available Decomposition temperature:	No data available
No data available Viscosity, kinematic:	No data available
No data available Viscosity, dynamic:	No data available
No data available	No data available

9.2. Other information

Minimum ignition energy : Typically >550 degrees celsius by Pinsky-Martens method

**SECTION 10****STABILITY AND REACTIVITY PROPERTIES****10.1. Reactivity**

Thermal decomposition generates: Corrosive vapors.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7). Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Fumes. Carbon monoxide. Carbon dioxide. May release flammable gases. Thermal decomposition generates: Corrosive vapors.

SECTION 11**TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

Acute toxicity: Not classified

hexamethylenetetramine (100-97-0)	
LD50 oral rat	> 5000 mg/kg (Rat)

Skin corrosion/irritation: Not

classified Serious eye damage/irritation:

Not classified Respiratory or skin sensitization:

Not classified

Germ cell mutagenicity: Not classified

Based on available data, the classification criteria are not met

Carcinogenicity: Suspected of causing cancer.

diatomaceous earth, uncalcined (61790-53-2)

IARC group	3 - Not classifiable
------------	----------------------

carbon black (1333-86-4)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------



Reproductive toxicity:	Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure):	Not classified
Specific target organ toxicity (repeated exposure): exposure. Aspiration hazard:	May cause damage to organs through prolonged or repeated Not classified
Potential Adverse human health effects and Symptoms:	Based on available data, the classification criteria are not met.

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

hexamethylenetetramine (100-97-0)	
LC50 fish 1	49800 mg/l (LC50; 96 h)
EC50 Daphnia 1	36000 mg/l (EC50; 48 h)

12.2. Persistence and degradability

BLACK EPOXY POWDER (COURSE/GLASS FILLED)	
Persistence and degradability	Not established.
hexamethylenetetramine (100-97-0)	
Persistence and degradability	Hydrolysis in water.
Biochemical oxygen demand (BOD)	0.026 g O ₂ /g substance
ThOD	1.37 g O ₂ /g substance (NH ₃)
BOD (% of ThOD)	0.01897
diatomaceous earth, uncalcined (61790-53-2)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

BLACK EPOXY POWDER (FINE/GLASS FILLED)	
Bioaccumulative potential	Not established.
hexamethylenetetramine (100-97-0)	
Log Pow	-4.15 - -2.13
Bioaccumulative potential	Bioaccumulation: not applicable.
diatomaceous earth, uncalcined (61790-53-2)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

No additional information available



12.5. Other adverse effects

Effect on the global warming: No known ecological damage caused by this product. Other information: Avoid release to the environment.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste disposal recommendations: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with all federal, state, and local health and environmental regulations.

Ecology - waste materials: Avoid release to the environment.

SECTION 14 TRANSPORT INFORMATION

Department of Transportation (DOT)

In accordance with DOT
Not regulated for transport
Additional information
Other information: No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15 REGULATORY INFORMATION

15.1. US Federal regulations

hexamethylenetetramine (100-97-0)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
diatomaceous earth, uncalcined (61790-53-2)
Listed on the United States TSCA (Toxic Substances Control Act) inventory
carbon black (1333-86-4)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)



15.3. US State regulations

carbon black (1333-86-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance level (NSRL)
Yes	No	No	No	

SECTION 16 OTHER INFORMATION

Indication of changes: Revision -
 See : *. Other information: None.
 Full text of H-phrases:

Carc. 2	Carcinogenicity Category 2
Flam. Sol. 2	Flammable solids Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H228	Flammable solid
H317	May cause an allergic skin reaction
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF. ASSUMES NO RESPONSIBILITY FOR PERSONAL INJURY OR PROPERTY DAMAGE TO VENDEES, USERS OR THIRD PARTIES CAUSED BY THE MATERIAL. SUCH VENDEES OR USERS ASSUME ALL RISKS ASSOCIATED WITH THE USE OF THE MATERIAL.