

MATERIAL SAFETY DATA SHEET

PRODUCT NUMBER: 10 99 19 / 10 99 26 / 10 99 36 / 10 99 46 / 10 99 20 / 10 99 30

SECTION 1 PRODUCT IDENTIFICATION AND MANUFACTURE

SUPPLIER: METPREP LTD.

CURRIERS CLOSE CHARTER AVENUE COVENTRY CV4 8AW

TELEPHONE: 024 7642 1222 FAX: 024 7642 1192

PRODUCT: Superthin Abrasive Cut off wheels

SECTION 2 SUBSTANCE HAZARD IDENTIFICATION

2.1 Precautionary statements

Use with adequate ventilation. Avoid breathing dust. Wash thoroughly after handling and use. Observe recommended operating speeds.

2.2 Description of Hazards

Dust may cause eye and respiratory irritation. Dust particles may cause abrasive injury to theyes. Using wheels in excess of recommended operating speeds may result in serious injury due to wheel breakage.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

The product contains the following ingredients which are classified according to Regulation (EC) Nr. 1272/2008 or for which a community occupational exposure limit value exists:

Ingredient	Formula	% Weight	OSHA Rgulated	CAS #
Aluminum Oxide	Al ₂ O ₃	0-95	N/A	1344-28-1
Silicon Carbide	SiC	0-95	N/A	409-21-2
Cured Rubber Compounds	N/A	1-20	N/A	N/A
Sulfur	S ₈	1-10	N/A	7704-34-9
Cured Phenolic Resin	N/A	0-10	N/A	N/A
Calcium Carbonate	CaCO ₃	0-5	N/A	1317-65-3
Calcium Oxide	CaO	0-5	N/A	1305-78-8
Potassium Aluminum Fluoride	KAIF4	0-5	N/A	14484-69-6
Patassium Fluoroborate	KBF4	0-5	N/A	14075-53-7
Iron Oxide	Fe ₂ O ₃	0-5	N/A	1309-37-1
Kaolin	Al ₂ Si ₂ O ₅ (OH) ₄	0-5	Yes	1332-58-7
Magnesium Sterate	Mg(C ₁₈ H ₃₅ O ₂) ₂	0-3	N/A	557-04-0

Page 1 of 4 Revision: 13.04.2016



SECTION 4 FIRST AID MEASURES

4.1 First Aid for exposure

Remove to fresh air, wash eyes with water, wash skin with soap and water, obtain first aid or medical assistance as deemed necessary.

4.2 Signs and Symptoms of Exposure

Could cause coughing and shortness of breath due to dust. May affect breathing, irritate eyes, and cause skin irritatin. Pre-existing respiratory disease may be aggravated

SECTION 5

FIRE FIGHTING MEASURES

- **5.1 Means Of Extinction:** Use any media that is appropriate for the surrounding fire.
- 5.2 Unusual Fire or Explosion Hazards: This product is not combustible. However, consideration must

Be given to the potential fire/explosion hazards from the base material being processed. Many materials explosive dusts or turnings when machined or ground.

5.3 Special Fire Fighting Procedures: None needed.

SECTION 6

ACCIDENTAL RELEASE MEASURES

Pick up, sweep up or vacuum and place in a container for disposal. Minimize generation of dust. Notify authorities as required by local, state and federal regulations.

SECTION 7

HANDLING AND STORAGE

- **7.1 Handling:** Use only with adequate ventilation. Avoid breathing dust. Wash thoroughly after handling and use, expecially before eating, drinking or smoking. Refer to ANSI B7.1 Safety Code for additional information. Consider potential exposure to components of the base materails or coasting being ground. Refer to OSHA's substance specific standards for additional work practice requirements where applicable.
- 7.2 Storage: Store in accordance with ANSI B7.1 Safety Code. Protect abrasive wheels from damage.

SECTION 8

EXPOSURE CONTROL/PERSONAL PROTECTION

8.1. Exposure limits

Chemical	OSHA PEL	ACFIH TLV
Aluminum Oxide	15 mg/m₃	10 mg/m₃
Silicon Carbide	15 mg/m₃	10 mg/m ₃
Cured Phenolic Resin	Not established	Not established
Cured Rubber Compounds	Not established	Not established
Sulfur	15 mg/m₃	10 mg/m ₃
Calcium Carbonate	15 mg/m₃	Not established
Calcium Oxide	5 mg/m₃	2 mg/m ₃
Potassium Aluminum Fluoride	2.5 mg/m₃	2.5 mg/m ₃
Potassium Fluoroborate (as fluorides)	2.5 mg/m₃	2.5 mg/m ₃
Iron Oxide	10 mg/m₃	5 mg/m ₃
Kaolin	5 mg/m ₃	10 mg/m ₃
Magnesium Stearate	Not established	10 mg/m ₃

Note: Consider also compounds of base materials and coatings being ground.

Page 2 of 4 Revision: 13.04.2016



8.2 Personal protection requirements and referrals

Respiratory: Use NIOSH approved respirator if exposure limits are exceeded or where dust exposures are excessive. **Ventilation:** Use local exhaust or general ventilation as required to minimize exposure to dust and maintain the

concentration of contaminants below the TLVs.

Protective Gloves: Cloth or leather gloves recommended.

Eye Protection: Safety goggles or face shield over safety glasses with side shields.

Hearing Protection: Elevated sound levels may result during operation. Use ear protection as necessary.

Hygienic Practices: Follow good general industrial safety practices during use.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point: Not applicable

Vapor Pressure: (mm Hg) Not applicable Vapor Density: (air = 1) Not applicable Solubility in Water: Insoluble

Lower And Upper Explosion Limits: Not applicable

Flash Point: Non-combustible

Specific Gravity: Not applicable Melting Point: Not applicable

Evaporation Rate: (Butyl Acetate=1) Not applicable **Appearance:** Black, green or reddish colored rigid wheel

Odor: None

SECTION 10

STABILITY AND REACTIVITY PROPERTIES

Stability: Stable

Incompatibility: None known.

Hazardous Decomposition Products: Dust from grinding could contain ingrediants listed in Section 3 and other, potentially more hazardous components of the base material being ground or coatings applied to the base material.

Hazardous Polymerization: Will not occur.

SECTION 11

TOXICOLOGICAL INFORMATION

11.1 Component information

Short term effects Lo Oral rat LD50 > 5,000 mg/kg N

Calcium Carbonate Oral rat LD50 = 6,450 mg/kg Potassium Aluminum Fluoride No data available Long term effects
No data available
Sarcinogen
Not carcinogenic
No data available
3 as listed by IARC

Component information

11.2 Route(s) of Entry and symptoms of exposure

See section 4.2

Aluminum Oxide

Chemical

SECTION 12

ECOLOGICAL INFORMATION

No ecological data is available for this product. No hazards to the environment are expected from this product.

However, consideration must be given to potential environment effects of the base material being processed.

Page 3 of 4 Revision: 13.04.2016



SECTION 13

DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable local, state/provincial and federal regulations. Local regulations may be more stringent than regional and national requirements. It is the responsibility of the waste generator to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations

SECTION 14

TRANSPORT INFORMATION

DOT Hazardous Materials Description: Not regulated

Proper Shipping Name: Not regulated

UN Number: None

Hazard Class/Packing Group: None

Labels Required: None

SECTION 15

REGULATORY INFORMATION

SARA Section 311/312 Hazard Categories: Not Applicable (manufactured articles)

SARA Section 313: Some products contain the following toxic chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (Toxic

Chemical Release Reporting): None

California Proposition 65: WARNING! You create dust when you cut, sand, drill or grind materials such as wood,

paint, cement, masonry or metal. This dust often contains chemicals known to cause cancer, birth defects or other

reproductive harm.

Canadian WHMIS Classification: Not a controlled product. This product meets the definition of a "manufactured article" under the WHMIS regulations. This product has been classified under the CPR and this MSDS discloses information elements required by the CPR.

SECTION 16

OTHER INFORMATION

The above information is based on our current standard of knowledge and does not constitute any warranty of conditions of the product. The information does not form part of any contractual agreement. It remains the user's responsibility to adhere existing laws and regulations.

Page 4 of 4 Revision: 13.04.2016